

SRET215H-10-D

DATA SHEET

RET H Line



RET H Line · Retractable Motorized Monitor

Double Screen Retractable Motorized Monitors made of anodized aluminium with beveled edges and protective glass with black border serigraphy.



SRET215H-10-D

SOLTEC TECHNICAL SPECIFICATIONS

RETRACTABLE MOTORIZED MONITOR RET H Line

GENERAL DESCRIPTION

Retractable Motorized 21.5" TFT monitor for boardroom and meeting room tables. Double screen with high-end anodized aluminium monitor housing with beveled edges. Protective glass with black border serigraphy.

If an obstruction is detected on the cover plate, the system stops and reverts the movement.

Brushed aluminium cover plate.

Monitor and cover plate can be customized with different finishings.

RS-232 serial control through DB9 connector.
RS-485/422 serial control through In/Out RJ45 connector allowing loop and addressing.

Full range of options available.

DISPLAY x 2

Panel Technology	IPS LED Technology
Display Area (mm)	476.64(H) x 268.11(V)
Size	21.5"
Pixel Pitch (mm)	0.248 x 0.248
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	89°/89°/89°/89°
Contrast Ratio	5000:1 (Typ)
Brightness cd/m2	300 (Typ)
Colors	16.7M Colors
Response Time	16ms Ton + Toff
Life Time (hours)	50.000
Protective Glass	3mm with black border

CONNECTIVITY

Analogue RGB Input	1xDB15
Digital Input	1xDVI-D
RS-232 Control	1xDB9
RS-485/422 Control	2xRJ45 (In/Out)

CONTROL

Remote Control	1xRS232, 1xRS485/422
Manual Control	2 Pushbuttons (Up/Down) 2 Pushbuttons (Tilt adjustment)

ELECTRICAL

Power Adaptor	90 ~ 264VAC to 12VDC 47 ~ 63Hz
Power Consumption	60W
Energy Management	VESA DPMS

MECHANICAL (SRET215H-10-D)

Screen Housing (mm)	545 x 337 x 40
On-table Cover Plate (mm)	639 x 105
Under-table Housing (mm)	622.5 x 623.5 x 93.5
NET Weight (Kg)	25
Packaging dimensions (mm)	730x720x190
Gross Weight (Kg)	27

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	5 to 90
Storage Humidity (%)	5 to 90

OTHERS

Certifications	CE; RoHS, BIS, EAC
Plug & Play	VESA DDC2Bi
Accessories	Mains Power Cord User Manual

ORDERING INFORMATION

SRET215H-10-D	Standard 21.5" RET-G Line
SRET215H-15B-D	Built-in Bosch Mic Delegate
SRET215H-15BC-D	Built-in Bosch Mic Chairman
SRET215H-15D-D	Built-in DIS/Shure Mic Delegate
SRET215H-15DC-D	Built-in DIS/Shure Mic Chairman
SRET215H-15T-D	Built-in Televic Mic Delegate
SRET215H-15TC-D	Built-in Televic Mic Chairman
SRET215H-15XLR-D	Built-in Generic XLR3 Mic

* Double microphone models: -16 instead of -15

Specifications subject to change without prior notice



SRET215H-10-D

SOLTEC
GENERAL DIMENSIONS

RETRACTABLE MOTORIZED MONITOR RET H Line

CONSULTANTS & ARCHITECTS

Technical product description

Retractable Motorized 21.5" TFT Monitor with double screen. Monitor housing made of anodized aluminium with beveled edges.

Built-in 3mm protective glass with black border serigraphy. Brushed aluminium cover plate.

Native resolution WXGA 1920x1080.

Two pushbuttons located on the cover plate for the up/down lift system.

VGA and DVI inputs. 1xRS-232 serial control through DB9 connector and 1xRS-485/422 serial control through RJ45 connector in loop and addressing. External power supply.



